



www.chinetekgroup.com call: [+852] 2319.2668

Established as a barcode solution provider since 1987, we entered the AIDC technology specifically aims to answer the many challenges posed by the security-conscious and mission-critical market.

Synergizing philips mifare contactless technology from 1992 onward, we have developed a full line of hardware and software products to answer those needs with a seamless, integrative, flexible and highly upgradable solution to companies in all sectors.

Supplemented by the customized software engine specifically designed to your specifications, your corporation can now tailor-made your own version of the "Smart Solutions" with our modules.

- Supports Microsoft Windows environment
- On-board OS for Stand-Alone Operation
- Sets of ".exe" modules are provided
- Built-in 2*16 back light LCD for interactive dialogue
- Built to withstand industrial environment
- Built-in buzzer and membrane keypad
- Built-in "Beep" & 3-Color LED indicator light
- Built-in Real Time Clock
- Built-in Output relays to control external devices
- Built-in 512K bytes EEPROM
- With user-friendly Access Control software
- AC-90R: Online & Offline Operation
- AC-90, AC-90i: Offline ONLY - lower server CPU system cost and minimizes downtime disaster



Dimension:
155mm x 110mm x 25mm



我們開發的產品建基於菲利浦MiFare非接觸式智能卡技術，本集團的業務迅速擴展，成為全系列智慧卡完整應用及解決方案的專業供應商。我們在智慧卡解決方案領域擁有強大的技術實力，成為本行業首屈一指的翹楚。

快捷、準確及安全，滿足日益增加的門禁及運輸的需求 - 有效、彈性，價值合宜的門禁方案

友善的軟件設計，提供貼身的方案是我們的優勢，我們會因應客人的獨特需求而修改我們的硬件和軟件以作配合。

great for: general office, factory system, beauty salon retail chain-store, karaoke, night club, sauna, tutoring center, cafeteria, deli, dormitory, school, library, motel, hotel, 5-star F&B chain, logistics, trucking, club-house, property management, pharmacy, medical clinic, hospital, college campus, fitness center, plaza owner

適用於辦公室、屋苑、實驗室、工廠、運輸會所等辦公室、工廠、零售連鎖店、酒店、高級食肆卡拉OK、夜總會、藥房、診所醫院、大學、飯堂、宿舍運輸、物流中心、高級會所、物業管理

AC-90 Series

smart card solution



- Specifications:**
- Philips Mifare 13.56MHz
 - Operating Distance: 60mm
 - Operating Temperature: 0-40 degree C
 - Interface: RS232/RS422/TCPIP Connectivity
 - Communication Baud Rate: 9600
 - Power Rating: 220VAC