

www.chinetekgroup.com call: [+852] 2319.2668

Established as a barcode solution provider since 1987, we entered the AIDC technology specifically aims to answer the many challenges posed by the security-conscious and mission-critical market.

Synergizing philips mifare contactless technology from 1992 onward, we have developed a full line of hardware and software products to answer those needs with a seamless, integrative, flexible and highly upgradable solution to companies in all sectors.

Supplemented by the customized software engine specifically designed to your specifications, your corporation can now tailor-made your own version of the "Smart Solutions" with our modules.

CT-820 Time Recorder

On-board OS for Stand-Alone Operation

Built-in 75mm x 40mm Chinese & English LCD display
Staff ID and Staff Name Display, Big5 or GB Chinese
Built-in Control Keys for easy Stand-alone setup
Built-in membrance function keys
Built-in Real-Time Clock for "Time Stamping" usage
Records 9999 RECORDS
Built-in 512K Bytes Flash (No Battery Required)
Programmable batch-by-interval data download
With user-friendly User Registration & System Interface
Active-X component - data-download via WEB Page
Sets of .EXE program for user development





我們開發的產品建基於菲利浦MiFare非接觸式智能 卡技術,本集團的業務迅速擴展,成為全系列智慧 卡完整應用及解決方案的專業供應商。我們在智慧 卡解決方案領域擁有強大的技術實力,成為本行業 首屈一指的翹楚。

友善的軟件設計,提供貼身的方案是我們的優勢, 我們會因應客人的獨特需求而修改我們的硬件和軟件以作配合.

Intelligently monitor and control your human resources and its related elements in logistics and delivery management with the CT-820 Time Recorder.

Designed to streamline the time-element of almost all versions of delivery workflow - the CT820 will help paint a better picture to monitor and operate your crew team. Through dependable data capture via mifare smart card and object-specific reports generated to meet the management needs, resource wastage will be reduced, productivity will be improved which results in higher revenue and better company image.

適用於辦公室、運輸、物流中心、高級會所 零售連鎖店、酒店、藥房、診所醫院、大學、宿舍

CT-820 Series smart card solution

Specifications:
Philips Mifare 13.56MHz
Operating Distance: 60mm
Operating Temperature: 0-40 degree C
Interface: RS232/RS422 & TCP/IP Connectivity
Communication Baud Rate: 9600
Power Rating: 200-240VAC